



ETSI WG TM6
(ACCESS TRANSMISSION SYSTEMS ON METALLIC CABLES)

Permanent Document

TM6(99)08 rev 9

Living List for Spectral Management

SpM - part 1

revision of TR 101 830-1

This document is the living list of current issues connected with ETSI's spectral management report TR 101 830, part 1 (*Definitions and Signal Library*).

The latest version (v1.2.1) of "part 1" has officially been published on august 28th 2001, by ETSI. This work is extended for including full signal descriptions for VDSL and ADSL-FDD (both "over POTS" and "over ISDN"). The current draft has achieved working group approval during the ETSI-TM6 meeting of sept 2002. This means that after passing an AbC procedure (approval by correspondence) the second revision of the SpM report can be published soon. Issues that are (still) under study, may be scheduled for a succeeding revision, to be decided in de November meeting. The issues related to "Part 2" and "Part 3" are beyond the scope of this living list.

<i>Work Item Reference</i>	DTS/TM-06020-1
<i>Permanent Document</i>	TM6(99)08
<i>Filename</i>	990p08a10.pdf
<i>Date</i>	Oct 4 th , 2002

Rapporteur/Editor	Rob F.M. van den Brink	tel: +31 70 4462389
	KPN Research	fax: +31 70 4463166 (or 4463477)
	PO Box 421	email: R.F.M.vandenBrink@kpn.com
	2260 AK Leidschendam	
	The Netherlands	

1. STUDY POINTS PART 1 (SIGNAL LIBRARY)

SP	Title	Owner	Status
1-1	Complete signal description for ADSL FDD over POTS	Peter Reusens (Alcatel)	Agreed
1-2	Complete signal description for ADSL FDD over ISDN	Peter Reusens (Alcatel)	Agreed
1-3	Complete signal description for ISDN-PRA		Deleted
1-4	Improvement of scope and legal status of report		Deleted
1-5	Review of peak amplitudes of all signals in the library		Deleted
1-6	Complete signal description for SDSL		Agreed
1-7	Review of power feeding issues	Rasmus Trevland - NPTA	Agreed
1-8	Complete signal description for ADSL ADL	Peter Reusens (Alcatel)	Under study
1-9	Harmonizing of spectral management Terminology	Rob Kirkby (BT)	Agreed
1-10	Definition of PSD Terminology	Paul Donaldson (Wcom)	Under Study
1-11			
1-12			
1-13			
1-14			

The current agreed procedure for changing the status of living list items is in Annex A of TM6 working methods.

Part 1 study points**SP 1-1. Complete signal description for ADSL FDD over POTS**

The ADSL standard is dedicated to echo cancelled systems, using signals with frequency overlap. FDD versions of ADLS, with no frequency overlap, do exist as proprietary systems, but are not (yet) covered by ETSI standards. As a result a signal description for Spectral Management purposes is lacking.

This study point is dedicated to define the description of a signal category for FDD versions of ADSL over POTS, which follows the ETSI standard that is being prepared for FDD versions of ADSL.

Status: Agreed

Related Contributions:

- *TD24, Sophia 2002 - Adding missing ADSL variants to SpM part 1 - Alcatel*
- *TD40, Praha 2002 - Editorial corrections - Alcatel*

SP 1-2. Complete signal description for ADSL FDD over ISDN

Similar to study point 1-1, but dedicated to ADSL-FDD over ISDN.

Status: Agreed

Related Contributions:

- *TD24, Sophia 2002 - Adding missing ADSL variants to SpM part 1 - Alcatel*
- *TD40, Praha 2002 - Editorial corrections - Alcatel*

SP 1-3. → *Obsolete*

SP 1-4. → *Obsolete*

SP 1-5. → *Obsolete*

SP 1-6. → *Obsolete*

SP 1-7. Review of power feeding issues

This study point is dedicated to improve some inconsistencies and ambiguities on the Power Feeding clauses. The current numbers are system dependent, while the power feeding issue is more related to (system independent) safety requirement.

The update of TR 101 830-1 (v1.2.1) has made this visible, by dedicating class "A" and "B" power feeding to (system independent) safety requirement, and by dedicating class "X" and "Y" to system dependent implementations. When the descriptions of class "A" and "B" have been completed, these classes "X" and "Y" may become obsolete. Contributions are invited.

Status: Agreed

Related Contributions:

- *TD20, Monterey 2000 - Modification of information on Feeding Power - NPTA*
- *TD13, Sophia 2001 - Modification of information on Feeding Power - NPTA*
- *TD16, Stockholm 2001 - Modification of text in clause 7 - NPTA*

SP 1-8. Complete signal description for ADSL ADL

This study point is dedicated to define a complete description of a signal category, as summarized in the informative annex E of the (draft) ADSL standard. That annex deals with characteristics of "all digital loop" signals

Status: Under Study

- *TD40, Praha 2002 - Editorial corrections to SpM part 1 - Alcatel*

SP 1-9. Harmonizing of spectral management Terminology

Currently, some inconsistent terminology is used in different , contributions and documents about spectral management "rules" and involved "bodies". This confuses SpM discussions. After some debate in TM6, the idea of using the following terminology was sounding:

Bodies: "loop provider" and "network operator" (The latter can be refined by prefixes like "incumbent" or "competitive" network operator, if required).

Rules: "deployment rules" and "access rules"

This study point is dedicated to generate relevant text for this terminology.

Status: Agreed

Related Contributions:

- *TD37, Torino 2002 - Harmonizing some terminology about Spectral Management - KPN*

SP 1-10. Definition of PSD Terminology

During the discussions in TM6 about VDSL PSD's, it became clear that concepts like PSD "masks" and "templates" are sometimes mixed up. The same applies for prefixes like "nominal" and "peak". Consistent terminology is lacking,

This study point is to generate relevant text for this PSD terminology, that is as close as possible to commonly used terminology and existing standards.

Status: Under study (see text attached to this living list, updated according to the latest views)

Related Contributions:

- *TD37, Torino 2002 - Harmonizing some terminology about Spectral Management - KPN*
- *TD30, Sophia 2002 - Definition of PSD masks end templates in T1E1.4 SpM doc - Adtran*
- *WD13, Praha 2002 - Operators need for nominal and peak PSD masks - many operators*

Text proposals, being candidate for inclusion into the Draft .

The text fragments below have been proposed for inclusion in the draft version of SpM part 1, but are still in the "under study" status. If agreement is achieved, they will be moved to the Draft.

Text portions proposed for inclusion into clause 3.1

The text fragments below about PSD's are still subject of debate

PSD: A signal characteristic in the frequency domain, equal to the Fourier transform of the autocorrelation of that signal. Due to the mathematical nature of this definition, a direct measurement of this quantity (according to the definition) is often impractical. PSD values can be estimated, however, from narrow band signal power measurements within a known resolution bandwidth (Wiener Khintchine theorem). These spectral measurements are only *approximations* of the PSD, unless the PSD is frequency independent within that resolution bandwidth. The definition of a PSD is independent of any resolution bandwidth, while spectral measurements require a specification of the resolution band being used.

Peak mask of a PSD: This is the absolute upper bound of a PSD, measured within a specified but relatively *narrow* resolution bandwidths; for instance 10 kHz for signals up to 1 MHz. The purpose of peak masks is often to specify spectrum management compliance, since it enables bounding of "worst case" values of a (single sided) PSD.

Nominal mask of a PSD: This is the absolute upper bound of a PSD, measured within a specified but relatively *wide* resolution bandwidth; for instance 100 kHz for signals up to 1 MHz. The purpose of peak masks is often to specify spectrum management compliance, since it enables bounding of "average" values of a (single sided) PSD. On the edges of PSDs, however, the nominal mask tend to be more capacious, due to the wider nature of the resolution band, and the meaning of their values becomes often limited within these frequency bands.

Template of a PSD: These levels represent nominal signal characteristics in the frequency domain, not related to any resolution bandwidth. It is intended to be a fair replica of a (single sided) PSD for modeling crosstalk and calculating noise margin. Template levels are often close to the levels of a nominal mask in frequency bands with flat PSD, but may deviate significantly from that nominal mask near the edges of PSDs.